



SANSIN PROTECTIVE MILLWORK COATING #P717/725

DESCRIPTION A concentrated aqueous, penetrating, low VOC coating. To be used as an undercoat for window joinery and millwork.

APPLICATIONS Recommended for use on new millwork products after being diluted with water in a ratio of 1:1.

CHARACTERISTICS

- ◆ Appearance..... Transparent Amber
- ◆ Odor..... Low
- ◆ Form Liquid
- ◆ Specific Gravity..... 1.00-1.02
- ◆ Density 8.42 lbs.
- ◆ Solid Content..... 24%
- ◆ pH, (approx.)..... 8.4-8.9
- ◆ Viscosity, 60cPs @20°C, Brookfield spindle #1, 60 RPM
- ◆ Solvents Low
- ◆ Diluent..... Water
- ◆ Cleanup..... Soap & Water
- ◆ Drying Time (To touch) @ 20°C (68°F)..... 4-6 Hours
- ◆ Coverage Pending to Penetration 200-300 sqft/USgal
- ◆ Keep from freezing

PRODUCT BENEFITS

- ◆ Water based
- ◆ Environmentally Safe
- ◆ Low VOC
- ◆ Non Flammable
- ◆ Water repellent
- ◆ Provides dimensional stabilization
- ◆ Penetrates the wood surface
- ◆ Low odor
- ◆ Does not discolor the wood
- ◆ No surface residues
- ◆ Will resist dirt and oil
- ◆ At normal temperatures will not precipitate components that will affect appearance or effectiveness of the treatment.

PACKAGING

Available in 5 US gallon plastic containers and bulk containers

APPLICATION METHODS

- ◆ Apply by dipping, vacuum coating and spraying.

WORKING PROCEDURE

- ◆ Apply the product evenly
- ◆ Applicable over millwork products with moisture content of 8-20%
- ◆ Allow 4–6 hours of drying time @ 20°C (68°F)
- ◆ Stir container lightly to raise eventually settled neutral material.
- ◆ Add water to the product applying moderate agitation.
- ◆ For best results dilute the product with water (15-20°C) in the ratio of 1:1.

STORAGE

Store at a temperature of between + 5°C and + 25 °C (41°F and 77°F).
Keep containers tightly closed.
Cover the dipping tank when not in use.

SAFETY

See Material Safety Data Sheet

WARNING TO USERS

Keep out of reach of children, If swallowed immediately drink two glasses of milk or warm water. Do not induce vomiting. Call physician immediately. Avoid contact with skin or eyes; flush with water and soap. Avoid breathing of vapor or mist.

The information contained in this document is given in good faith based on our current knowledge. The use of the product is beyond the control of The Sansin Corporation, and no guarantees, expressed or implied, are made as to the result to be obtained if not used in accordance with the published Directions for Use.

The Sansin Corporation does not assume any legal responsibility for use or reliance on same.

This information must on no account be used as a substitute for necessary field tests, which alone can ensure that the product is suitable for the expected use. Before using any product, read its label.

March 2001