



PURITY INTERIOR CLEAR ARCTIC

DESCRIPTION An ultra clear aqueous, low VOC, fast drying, interior wood finish. Prevents yellowing of wood. Normally 2-3 coats are required. It is recommended to use Purity Interior Clear Arctic Gloss for the first two coats and use Gloss, Satin or Flat as the final coat only. This will improve hardness and clarity. Purity Interior Clear Arctic is available in Gloss, Satin and Flat.

APPLICATIONS Recommended for interior use on new and old wood substrates such as log walls, timber frames, cabinetry, shelves, doors and windows, base boards, interior siding, furniture, ceilings and walls.

CHARACTERISTICS

- ◆ Appearance.....Transparent, Slight Milky
- ◆ Coloring.....Clear, Non Yellowing
- ◆ Odor..... None
- ◆ Form Liquid
- ◆ Specific Gravity..... 1.00-1.01
- ◆ Density 8.34-8.42Lb/gal
- ◆ Solid content.....30%
- ◆ pH.....8.2-8.4
- ◆ Viscosity, #4 ZAHN Cup, 20°C (68°F) 15-16 Sec.
- ◆ SolventsLow
- ◆ Freezing Point-1°C (31°F)
- ◆ Diluent..... Water
- ◆ Cleanup..... Soap & Water
- ◆ Drying Time @ 20°C (68°F)..... 30 Minutes
- ◆ Drying Time(Between applications) @ 20°C (68°F)..... 2 Hours
- ◆ Coverage...first coat-300sqft/Us gal, second coat-400sqft/USgal
- ◆ Longer drying time needed in high humidity or low temperature
- ◆ Keep from freezing
- ◆ Application Temperature.....10-25°C

PRODUCT BENEFITS

- ◆ Breathing (Interior)
- ◆ Environmentally Sound
- ◆ Develops rapid hardness
- ◆ Low VOC
- ◆ Non Flammable
- ◆ High clarity and retains wood's character
- ◆ Non yellowing and good chemical resistance
- ◆ Water and dust repellent and stain resistant

- ◆ Fast drying and Low odor
- ◆ Cleanable with wet cloth

PACKAGING Available in Quarts, 1, 3 and 5 US gallon plastic containers

PREPARATION

- ◆ Wood must be dry
- ◆ Cover or remove all hardware
- ◆ Make necessary repairs
- ◆ Sand the wood surface
- ◆ Clean wood surface properly

APPLICATION METHODS

- ◆ Apply with a good quality nylon, polyester brush or pad

WORKING PROCEDURE

- ◆ Apply only on dry wood
- ◆ Apply finish consistently
- ◆ Apply first coat with a nylon, polyester brush or pad applicator
- ◆ Do not overwork the product
- ◆ Allow 2 hours of drying time @ 20°C (68°F)
- ◆ Sand lightly with 220 grit sandpaper
- ◆ Apply second coat
- ◆ **See published Directions For Use**

STORAGE Store at a temperature of between + 2°C and + 25 °C (36°F and 77°F).
Keep containers tightly closed.

SAFETY See Material Safety Data Sheet

WARNING TO USERS Keep out of reach of children, If swallowed immediately drink two glasses of milk or warm water. Do not induce vomiting. Call physician immediately. Avoid contact with skin or eyes; flush with soap and water. Avoid breathing of vapor or mist.

The information contained in this document is given in good faith based on our current knowledge. The use of the product is beyond the control of The Sansin Corporation, and no guarantees, expressed or implied, are made as to the result to be obtained if not used in accordance with the published Directions for Use. The Sansin Corporation does not assume any legal responsibility for use or reliance on same. This information must on no account be used as a substitute for necessary field tests, which alone can ensure that the product is suitable for the expected use. Before using any product, read its label.