



## PURITY INTERIOR STAIN

---

**DESCRIPTION** A penetrating, aqueous, low VOC, interior wood stain. Purity Interior Stain is a water borne alkyd that applies and flows easily without streaking or overlap. Purity Interior Stain is available as a clear sealer formula for surfaces where a non film forming coating is desired to enhance character & natural protection. For film form coatings use Purity Interior Clear or Purity Interior Clear Arctic.

---

**APPLICATIONS** Recommended for use on new and aged interior wood substrates such as log walls, timber frame, beams, cabinetry, furniture, ceilings and walls.

---

**CHARACTERISTICS**

- ◆ Appearance..... Transparent
- ◆ Coloring.....Standard and Custom
- ◆ Odor.....Low
- ◆ Form ..... Liquid
- ◆ Specific Gravity..... 1.00-1.02
- ◆ Density ..... 8.3-8.4
- ◆ pH, ( approx. ) ..... 8.8-9.0
- ◆ Viscosity, #4 ZAHN Cup, 20°C (68°F) ..... 48-52 Sec.
- ◆ Solvents .....Low
- ◆ Freezing Point ..... -1° (31°F)
- ◆ Diluent..... Water
- ◆ Cleanup..... Soap & Water
- ◆ Drying Time ( To touch ) @ 20°C (68°F)..... 4 Hours
- ◆ Drying Time( Between applications ) @ 20°C (68°F). 24 Hours
- ◆ Coverage Pending to Penetration .....200-400 sqft/USgal
- ◆ Longer drying time needed in high humidity or low temperature
- ◆ Keep from freezing

---

**PRODUCT BENEFITS**

- ◆ Environmentally Sound
- ◆ Breathing
- ◆ Low VOC
- ◆ Non Flammable
- ◆ Provides a uniform color
- ◆ Water repellent
- ◆ Penetrates the wood surface
- ◆ Fast drying
- ◆ Low odor

**PACKAGING**

Available in Quarts, 1, 3 and 5 US gallon plastic containers

---

**PREPARATION**

- ◆ Cover or remove all hardware
  - ◆ Make necessary repairs
  - ◆ Sand the wood surface
  - ◆ Clean wood surface properly
- 

**APPLICATION METHODS**

- ◆ Apply with a good quality nylon, polyester brush or pad applicator.
- 

**WORKING PROCEDURE**

- ◆ Apply finish consistently
  - ◆ Do not overwork the product
  - ◆ Apply only on dry wood
  - ◆ Allow 4 hours of drying time @ 20°C (68°F)
  - ◆ Sand lightly with 220 grit sandpaper
  - ◆ Apply second coat of Purity Interior Stain if desired
  - ◆ Apply 1 or 2 coats of Purity Interior Clear-UV in satin or gloss
  - ◆ **See published Directions For Use**
- 

**STORAGE**

Store at a temperature of between + 2°C and + 25 °C (36°F and 77°F).  
Keep containers tightly closed.

---

**SAFETY**

See Material Safety Data Sheet

---

**WARNING TO USERS**

Keep out of reach of children, If swallowed immediately drink two glasses of milk or warm water. Do not induce vomiting. Call physician immediately. Avoid contact with skin or eyes; flush with soap and water. Avoid breathing of vapor or mist.

The information contained in this document is given in good faith based on our current knowledge. The use of the product is beyond the control of The Sansin Corporation, and no guarantees, expressed or implied, are made as to the result to be obtained if not used in accordance with the published Directions for Use. The Sansin Corporation does not assume any legal responsibility for use or reliance on same. This information must on no account be used as a substitute for necessary field tests, which alone can ensure that the product is suitable for the expected use. Before using any product, read its label.

March 2004