



## TIMBER-TEC C-20 & M-30

---

**DESCRIPTION** Sansin Industrial Timber-Tec is a concentrated, penetrating wood protection system, offering an effective guard against weathering, providing active UV protection. Sansin Industrial Timber-Tec is available in two transparent formulas: # M-30, a light colored concentrate, retaining the natural light color of fresh pine, etc. and # C-20, a clear concentrate. Sansin Timber-Tec contains solids that penetrate well, creating dimensional stability and water repellency. Sansin Timber-Tec provides active UV protection “keeping” wood cleaner during the construction phase.

---

**APPLICATIONS** The application of Sansin Timber-Tec is suggested for use on logs, timbers and wood joinery products that are subject to weathering. Sansin Timber-Tec is intended as a priming application that should be applied to clean substrates that are not in ground contact. Sansin Timber-Tec can not be applied over previously finished wood.

- 
- CHARACTERISTICS**
- ◆ Appearance..... Transparent
  - ◆ Coloring..... Standard
  - ◆ Odor..... Low
  - ◆ Form ..... Liquid
  - ◆ Specific Gravity..... 1.02
  - ◆ Density .....8.05 Lb/gal
  - ◆ pH, (approx.) ..... 8.8
  - ◆ Viscosity, Brookfield (up to, 60RPM) @20°C.....10cPs
  - ◆ Solvents ..... Low
  - ◆ Freezing Point .....-1°C (31°F)
  - ◆ Diluents ..... Water
  - ◆ Cleanup..... Soap & Water
  - ◆ Drying Time (To touch) at 20°C (68°F) ..... 6 Hours
  - ◆ Coverage Pending to Penetration ..... 150-200 sq.ft./US gal
  - ◆ Longer drying time needed in high humidity or low temperature
  - ◆ Keep from freezing

- 
- PRODUCT BENEFITS**
- ◆ Concentrated (dilute 1:1 with water)
  - ◆ Environmentally sound
  - ◆ User friendly
  - ◆ UV protection
  - ◆ Water repellent Timber-Tec
  - ◆ Protection against weathering.
  - ◆ Deep wood penetration
  - ◆ Low VOC
  - ◆ Molecularly compatible, creating a monolithic bond with the wood

- ◆ Reduces warping, shrinking, checking
- ◆ Retains wood's natural color
- ◆ Non flammable
- ◆ High in solids
- ◆ Breathable
- ◆ Can be applied on damp or green lumber
- ◆ Clean-up with water and soap

**PACKAGING**

Available in 5 US gallon containers, 50 US gallon drums and totes.

**PREPARATION**

- ◆ Inspect wood surface for defects
- ◆ Cut, glue, machine and shape wood as desired, then power wash surface with minimum 2500 psi
- ◆ Where millglaze is evident, sand entire surface and power wash lightly
- ◆ Draw knifing and adzing are effective methods of preparing logs and timber for application of Sansin Timber-Tec. Ensure that application is done immediately afterwards, on the same day and out of direct sun if the wood is dry. On dry wood it is preferable to apply out of direct sunlight. On wet wood apply in direct sunlight as the finish will dry slowly, otherwise you risk washing it off if precipitation occurs.

**APPLICATION METHODS**

- ◆ Vacuum system (Pressure treating)
- ◆ Dipping
- ◆ Flood coating or roller coating ( manual or automatic)
- ◆ Spraying: Hand or automated spraying and back brushing
- ◆ Brushing or rolling
- ◆ Ensure a flood application in all circumstances.

**COVERAGE**

100-200 sq.ft./U.S. gallon. Coverage through saturation should be achieved. Because of the variation in porosity of wood substrates, coverage will range from 100-200 sq.ft. (9.3-18.6 sq.m.) per US gallon.

**STORAGE**

Store at a temperature of between +2°C and 25°C (36°F and 77°F).  
Keep containers tightly closed.

**SAFETY**

See Material Safety Data Sheet

**WARNING TO USERS**

Keep out of reach of Children. If swallowed immediately drink two glasses of milk or warm water. Do not induce vomiting. Call physician immediately. Avoid contact with skin or eyes; flush with soap and water. Avoid breathing of vapor or mist.

The information contained in this document is given in good faith based on our current knowledge. The use of this product is beyond the control of The Sansin Corporation, and no guarantees, expressed or implied, are made as to the result to be obtained if not used in accordance with the published Directions for Use. The Sansin Corporation does not assume any legal responsibility for use or reliance on same. This information must on no account be used as a substitute for necessary field tests, which alone can ensure that the product is suitable for the expected use. Before using any product, read its label.